



Product Service

# CERTIFICATE

No. Z1A 085212 0224 Rev. 05

**Holder of Certificate:** **NINGBO COMEN ELECTRONICS TECHNOLOGY CO., LTD**  
No.599 Jinda Road Zhenhai Economic Development Zone  
315221 Ningbo  
PEOPLE'S REPUBLIC OF CHINA

**Certification Mark:**



**Product:** **Multiple Socket Outlets**  
**Tested according to:** DIN VDE 0620-1:2016/A1:2017  
DIN VDE 0620-2-1:2016/A1:2017  
DIN VDE 0620-2-1:2021 Abschnitt 10.5  
AfPS GS 2019:01 PAK  
EK1 510-11  
EK1 702-20 Rev. 1

The product meets the safety and health requirements of the German Product Safety Act section 20 to 22 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 704101826112-05

**Valid until:** 2023-11-27

**Date,** 2021-04-30

( Jie Zhu )

# CERTIFICATE

No. Z1A 085212 0224 Rev. 05

**Model(s):** PMS-GEa-bc, PDU-GEa-bc

Variant 'a' stands for the series number

'a' = 1; 2; 5; 6; 7; 8; 9; A; J

1: 1st range, Al tube, flat cover

2: 2nd range, PVC tube, flat cover

5: 5th range, Al tube; round cover

6: 6th range, PVC tube; round cover

7: 7th range, Al tube; curve cover

8: 8th range, Al tube; table curve cover

9: 9th range, Al tube; with CBE construction

A: 10th range, PVC tube; with CBE construction

J: J range, Al tube; table rotate cover

Variant 'b' stands for the number of socket-outlets

'b' = 2; 3; 03; 04; 05; 06; 07; 08; 09; 10

2: with 2-way 2.5A socket-outlets

3: with 3-way 2.5A socket-outlets

03: with 3-way Schuko socket-outlets

04: with 4-way Schuko socket-outlets

05: with 5-way Schuko socket-outlets

06: with 6-way Schuko socket-outlets

07: with 7-way Schuko socket-outlets

08: with 8-way Schuko socket-outlets

09: with 9-way Schuko socket-outlets

10: with 10-way Schuko socket-outlets

Variant 'c' stands for the function modules

'c' = any combination of K; K2; S; D; D2; G; U2; U2A;

U3; U3A; U3B; N; M; S1

K: with a switch

K2: with two switches

S: with shutter

D: with SPD(model:PMS)

D2: with SPD(model:D-02)

G: with circuit breaker

U2: with 2A USB charger

U2A: with 2.4A USB charger

U3: with 3A USB charger

U3A: with 3.4A USB charger and 2 jacks

U3B: with 3.4A USB charger and 3 jacks

N: with network jack(RJ45)

M: with master-slave function

S1: with power meter and shutter



# CERTIFICATE

No. Z1A 085212 0224 Rev. 05

## Parameters:

Rated voltage:	250V~
Rated frequency:	50Hz
Rated current:	16A
Protection class:	I
Degree of protection:	IP20
Type of cable:	H05VV-F 3G1.5mm <sup>2</sup>
Remark:	DIN VDE 0620-2-1:2021 Abschnitt 10.5 is applicable for models with shutter